

C8000 EWX

8000LB 12V/24V ELECTRIC WINCH

Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing. Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated



STANDARD ACCESSORIES

- 29m x 8.3mm steel cable
- 3m Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

SPECIFICATION

RATED LINE PULL: 8000lbs (3629kg) **MOTOR:** 12v: 4.6hp / 3.2kw

GEARING: 210:1

BRAKING ACTION: Automatic in the drum

DRUM SIZE Dia x L: 63 x 223mm CABLE Dia x L: 8.3mm x 29m MOUNTING PATTERN: 254 x 114.3mm DIMENSIONS: 540 x 160 x 219mm

TECHNICAL PERFORMANCE

Layer of	Line pull		
wire rope	lbs (kg)		
1	8000 (3636)		
2	6529 (2962)		
3	5515 (2502)		
4	4773 (2165)		

Line pull	Line speed		Amp draw	
lbs (kg)	ft/min	m/min	12v	24v
0	32	9.8	80	60
3000 (1361)	11.5	3.5	190	150
5000 (2268)	9.1	2.8	260	220
8000 (3629)	6	1.8	360	300